

Proven to reduce 99.98% of SARS-CoV-2 virus (the virus that causes COVID-19) on surfaces within 7 hours.

THE TECHNOLOGY

The Aerus Mid-Range Blaster is a device intended for the reduction of viruses, bacteria, and other contaminants in large indoor spaces up to 5,000 sq. ft. (464m²). It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in "The Proof" section below). The Blaster was originally designed for spaces up to 20,000 sq. ft. (1858m²), but in light of the Delta variant, which has been reported to be 4 or more times more contagious than previous SARS-CoV-2 strains, we have adjusted our sizing guidelines and now recommend using the Blaster for a maximum of 5,000 sq. ft. (464m²).

ActivePure does not replace the need to follow public health guidelines and should be used as complementary technology.

· Listeria monocytogenes

· Sclerotinia sclerotiorum

· Aspergillus versicolor

· Candida auris

· Botrvtis cinerea

 Aspergillus niger endospores

· Methicillin-resistant

Staphylococcus

· Staphylococcus

epidermidis

epidermis

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens:

- · SARS-CoV-2 RNA Virus
- H1N1 Influenza
- H5N8 Influenza
- Murine Norovirus
- PhiX-174
- MS2 Bacteriophage
- MRSA
- E. coli
- · Salmonella enterica
- · Legionella pneumophila
- · Clostridium difficile
- · Bacillus globigii
- · Erwinia herbicola

THE BENEFITS

The Aerus Mid-Range Blaster provides surface decontamination and air purification without the use of ozone or other harmful chemicals. It is a proactive and effective solution for your home or business.

- New and improved ActivePure Technology delivers world-class surface decontamination and air purification technology
- Over a decade of testing, patented ActivePure® Technology
 has been proven to reduce over 99.9% of many common
 airborne and surface contaminants including viruses, bacteria,
 mold, fungi, VOCs, smoke, allergens, and odors (full list of
 tested pathogens available in "The Proof" section)
- · Quickly works to clean the indoor environment



SPECIFICATIONS

Product Information	00667 Model F203C* This unit does not meet California requirements and cannot be shipped to California.
Technology Included	ActivePure [®]
Electrical	Input Voltage: 120V Power Consumption: 172W
Mechanical	Fuse: 2.25A; 2.0A slowblow Airflow Rate: 300 CFM
Weight & Dimensions	24 lbs (10.9 kg) (unpackaged) 13"W x 22"H x 13"D (33.02 cm x 48.26 cm x 33.02 cm)
Noise Level	57.4 dB(A)
Recommended Maximum Coverage in a Contiguous Space ¹	Up to 5,000 sq. ft. (464m²) depending on occupant density and other factors¹.
Warranty	Limited 3 Year Warranty
	Contact Name:
	Email:
	Phone Number:

^{1.} Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, other layers of protection, and worst case desired outcomes. Testing actual application results before and after utilization of the technology, in as near as possible identical conditions, is a recommended measure to optimize effective deployment.